

What is claimed is:

- 1) A personal care product comprising a composite of a film layer and a co-extruded foam layer.
- 2) The product of claim 1 wherein said film layer is a breathable film.
- 5 3) The product of claim 1 wherein said foam layer comprises superabsorbent.
- 4) The product of claim 1 wherein said foam comprises elastic polymer in an amount between 75 and 95 weight percent and superabsorbent in an amount between 5 and 25 weight percent.
- 10 ~~5) The product of claim 4 wherein said superabsorbent is in a form selected from the group consisting of particles, fibers, and foams.~~
- 6) The product of claim 1 further comprising a nonwoven layer adjacent said foam layer.
- 7) The product of claim 5 wherein said nonwoven layer is selected from the group consisting of spunbond webs, meltblown webs, bonded-carded webs, airlaid webs, and laminates thereof.
- 15 8) The product of claim 1 further comprising a nonwoven layer adjacent said film layer.
- 9) A diaper comprising the composite of claim 1.
- 10) A training pant comprising the composite of claim 1.
- 11) An incontinence product comprising the composite of claim 1.
- 12) A bandage comprising the composite of claim 1.
- 20 13) A surgical gown comprising the composite of claim 1.
- 14) A patient drape comprising the composite of claim 1.
- 15) A sanitary napkin comprising the composite of claim 1.
- 16) A personal care product comprising a multilayer laminate including a nonwoven liner layer, co-extruded foam and film layers, and a nonwoven outercover layer.

17) A thermoformed diaper comprising a film layer and a coextruded foam layer, molded for a time under sufficient heat and pressure in a cup-shaped mold.

Sub  
Q27  
18) A method of making a composite for personal care products comprising the steps of extruding a film composition and co-extruding therewith a foam composition to form a composite material.

5  
19) The method of claim 18 further comprising the steps of laminating a nonwoven layer to either side of said composite material.

Sub  
B27  
10  
20) The method of claim 18 further comprising the step of thermoforming said composite in a mold having a shape, for a time and under heat and pressure sufficient to cause said composite to maintain the shape of said mold.

Sub  
Q37  
21) The method of claim 20 further comprising the step of sealing a seam formed by at least two parts of said composite.

Sub  
B27  
add B27  
22) The method of claim 21 wherein said seam is sealed ultrasonically.